

Product information

Meguin Fuel System Cleaner



Description

Highly effective combination of active agents for cleaning and protection. This product is formulated in accordance with the latest standard of fuel and additive technology and meets the requirements of today's engines, fuels and running conditions. It is suitable for all gasoline fuel injection systems such as K-; KE- and L- Jetronic systems, etc. For rectifying problems such as difficulties with starting, irregular idling, poor throttle response, performance losses, surges due to lean mixture and poor exhaust values caused by contaminated injection systems. Repeat treatment if problems reoccur. It is suitable for all gasoline injection systems.



Properties

- removes carbon deposits from intake valves and combustion chamber
- tested for the use with catalytic converters
- normalizes gasoline consumption and exhaust emissions
- cleans the injection system

Characteristic data

Base	additive mixture in liquid carrier
Color / appearance	light yellow, clear
Regulation on Flammable Liquids Class (Germany)	A II
Flash point	>61 °C
Pour point	-45 °C
Form	liquid
Odor	characteristic
Viscosity at 40 °C	<7 mm ² /s
Density at 15 °C	0,765 g/cm ³

Application

One 250ml can is sufficient for up to 50 litres of fuel. This product is effective over 2000 km. Fuel System Cleaner can be mixed with fuel at any time since mixing is spontaneous.

Available pack sizes

250 ml Can sheet metal	6550 GB-D-F-RUS-ARAB
250 ml Can sheet metal	33076 ALGERIEN-F-GB-D