

Product information

megol Motorenoel Fuel Economy SAE 5W-30



Description

High performance motor oil based on HC synthetic technology with a latest generation additive system (Low-SAPS technology and reduced HTHS). For maximum fuel savings and efficiency. Meets the high performance requirements of modern gasoline and diesel engines and ensures maximum service life of the diesel particulate filter as well as low wear, good engine cleanliness and long oil change intervals.

Range of applications: Passenger cars.

SAPS level: Low-SAPS.

Note the manufacturer's instructions!

Specifications / Approvals

ACEA C2 • ACEA C3 • API SP

Meguin also recommends this product for vehicles that are subject to the following specifications

Peugeot Citroen (PSA) B71 2290 • Fiat 9.55535-S1 • Honda • Mazda • MB 226.52 • MB 229.52 • Renault RN 17 • Toyota

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,855 g/cm ³ DIN 51757
Viscosity at 40 °C	60,5 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	10,3 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D5293
Viscosity index	159 DIN ISO 2909
HTHS at 150°C	≥ 2,9 mPas ASTM D5481
Pour point	-39 °C DIN ISO 3016
Evaporation loss (Noack)	9,7 % CEC-L-40-A-93
Flash point	230 °C DIN ISO 2592
Total base number	7,4 mg KOH/g DIN ISO 3771

Characteristic data

Sulfate ash	≤ 0,8 g/100g DIN 51575
Color number (ASTM)	L2,5 DIN ISO 2049

Available pack sizes

1 l Canister plastic	9440 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	9441 D-GB-F-ARAB-RUS-RO-I-E-P
20 l Canister plastic	9442 D-GB
60 l Black plate barrel	9443 D-GB
200 l Black plate barrel	9444 D-GB
1.000 l Deposit container	9735 D-GB
1 l Bulk goods	9445 D