

Product information

megol Special Engine Oil SAE 5W-30



Description

Modern high-performance motor oil. Thanks to the selected HC base oils in combination with the suitable additives, it has optimum properties specially formulated for gasoline engines on the Asian and American markets. Keeps the engine clean, offers high shear stability and minimizes wear. Ensures rapid oil penetration and smooth engine running under all operating conditions. Is thus very well suited for the high demands of modern engines. Note the manufacturer's instructions!

Specifications / Approvals

API SP • ILSAC GF-6A

Meguin also recommends this product for vehicles that are subject to the following specifications

Chrysler MS-6395 • Fiat 9.55535-CR1 • Ford WSS-M2C 946-A • Ford WSS-M2C 946-B1 • Ford WSS-M2C 961-A1 • GM 6094 M • GM dexos1 Gen 3 • Honda • Mazda • Mitsubishi Dia Queen • Nissan • Toyota

Characteristic data

SAE class (engine oils)	5W-30 SAE J300
Density at 15 °C	0,85 g/cm ³ DIN 51757
Viscosity at 40 °C	60 mm ² /s ASTM D 7042-04
Viscosity at 100 °C	10 mm ² /s ASTM D 7042-04
Viscosity at -35 °C (MRV)	< 60000 mPas ASTM D 4684
Viscosity at -30 °C (CCS)	≤ 6600 mPas ASTM D 5293
Viscosity index	155 DIN ISO 2909
HTHS at 150°C	> 2,9 mPas ASTM D 5481
Pour point	-45 °C DIN ISO 3016
Evaporation loss (Noack)	9,5 % CEC-L-40-A-93
Flash point	220 °C DIN ISO 2592
Total base number	9 mg KOH/g DIN ISO 3771
Sulfate ash	0,9 g/100g DIN 51575



Characteristic data

Color number (ASTM)	L 3,5 DIN ISO 2049
---------------------	-----------------------

Available pack sizes

1 l Canister plastic	33100 D-GB-F-ARAB-RUS-RO-I-E-P
4 l Canister plastic	33101 D-GB-F-ARAB-RUS-RO-I-E-P
5 l Canister plastic	33102 D-GB-F-ARAB-RUS-RO-I-E-P
20 l Canister plastic	33103 D-GB
60 l Black plate barrel	33104 D-GB
200 l Black plate barrel	33105 D-GB